

## Ordering guide

Example: PTH2270 P3 A

| Product Code   | Post Diameter                                      | Finish                                                                                  |
|----------------|----------------------------------------------------|-----------------------------------------------------------------------------------------|
| <b>PTH2270</b> |                                                    |                                                                                         |
| PTH2270 Triple | <b>P3</b> 3" Post Mount<br><b>P4</b> 4" Post Mount | <b>A</b> Black<br><b>B</b> White<br><b>G</b> Verde<br><b>H</b> Bronze<br><b>J</b> Green |

Project: \_\_\_\_\_

Location: \_\_\_\_\_

Cat.No: \_\_\_\_\_

Type: \_\_\_\_\_

Lamps: \_\_\_\_\_ Qty: \_\_\_\_\_

Notes: \_\_\_\_\_

## Specifications

### Housing

356 HM high-strength, low-copper, proprietary cast aluminum alloy.

### Finish


Thermoset polyester powdercoat is electrostatically applied after a five-stage conversion cleaning process and bonded by heat fusion thermosetting. Laboratory tested for superior weatherability and fade resistance in accordance with ASTM B117 specifications. For larger projects where a custom color is required, contact the factory for more information.

### Mounting

Cast Aluminum Hub mounts to a 3" OD x 3" long (P3) [if applicable] or 4" OD x 6 1/2" long (P4) [if applicable] tenon and is secured with at least (3) 5/16"-18 stainless steel set screws.

### Warranty

Three-year limited warranty.



| Height             | Length              | EPA          |
|--------------------|---------------------|--------------|
| 17 1/2"<br>(44 cm) | 41 1/2"<br>(105 cm) | 1.62 sq. ft. |