



Black



White



The Chloride new 55S Series LED exit sign delivers a powerful combination of style and performance in a die-cast aluminum housing. Its high-strength construction ensures long-term durability, while energy-efficient LEDs provide bright, uniform illumination throughout. Designed with maximum flexibility in mind, the 55 Series offers field-selectable red or green LEDs, red/green stencils, single and double face configurations, universal mounting, and field-selectable chevron indicators — making it one of the most adaptable exit signs available. Built to handle virtually any installation, it mounts seamlessly on ceilings, walls, or end-mount configurations.

Project: _____

Location: _____

Cat.No: _____

Type: _____

Lamps: _____ Qty: _____

Notes: _____

Ordering guide

Example: 55SE3B

Family	AC/Emergency	No of Faces	Housing Finish
55S			
55S 55 Series with Selectable red/green LED	A AC Only E Emergency	3 Universal	B Matt black with brushed aluminum face W White

Accessories

PVS2 Polycarbonate Vandal Shield

WG4 Wire Guard

Specifications

Lamp

- Field selectable bright red/green energy efficient LED lamps.
- Uniform 6" letter illumination (3/4" stroke) with knockout chevron directional arrows

Electrical:

- Input voltage: Universal 120~277VAC, 50/60Hz
- Input Power: 1.2W
- Battery low voltage protection
- Solid-state transfer circuit

Battery:

- Maintenance-free, rechargeable LiFePO4 battery
- Provides 90 minutes of emergency illumination
- Standard self-diagnostics/self-test
- Test Switch / Charge Indicator light

Codes and compliance:

- UL 924
- NFPA 70 (National Electric Code)
- NFPA 101 (Life Safety Code)
- CEC title 20
- Suitable for damp location
- AC version suitable for -25°C ~ 50°C (-13°F ~ 122°F) ambient temperature
- EM version is suitable for 5°C ~ 50°C (41 ~ 122°F) ambient temperature

Warranty:

- Five years limited warranty on electronics, LEDs and battery.

55S LED Lit Selectable Exit Sign

Exit and Emergency

Specifications

Construction:

- Die-cast aluminum housing\
- Compact and decorative design with easy replacement pictogram design
- Single and double face universal package
- Suitable for wall, side and ceiling mounting
- Pop-out chevron directional indicators are easily removed when required
- All exits are provided with an extra stencil face plate for double face sign applications

Surface Dimensions

