



Slim, sturdy and selectable

The DSRT Selectable Troffer combines robust construction, a slim design, and low glare for versatile applications.

Day-Brite/CFI DSRT Selectable Troffer is a robust low glare luminaire designed to provide three lumen and three CCT field selectable options per size. Available for use in recessed, suspended and surface mount applications. Ideal for general lighting applications such as open office, schools, healthcare, and retail.

DesignLights Consortium qualified
Please see the DLC QPL list for exact catalog numbers (<http://www.designlights.org/QPL>)

DSRT Selectable Troffer

Selectable lumens & CCT

Features

- **Color selectable:**
3500/4000/5000K @ 80 CRI
- **Lumen selectable:**
 - 1x4: 3000/4000/5000lm
 - 2x2: 3000/4000/5000lm
 - 2x4: 4000/5000/6000lm
- **Voltage:** 120-277V (UNV)
- **Housing:** Less than 3in depth
- **Dimming:** 0-10V
- **Sensor:** Daylight & Occupancy



Ordering guide

Example: 2DSRT4060L8CS-4-UNV-DIM-EM10RM

Family	Lumens (nom.)	CRI/CCT	Length	Diffuser	Voltage	Dimming	Options
1DSRT	3050L 3000/4000/5000	CS 3500/4000/5000	4 4 ft	Blank Round Diffuse	UNV Universal, 120-277V	DIM 0-10V driver	F1 ¹ 3/8" flex, 18 ga. 6'; 3 leads (hot, neutral, ground) does not include dimming leads
2DSRT	3050L 2800/3500/4200	CS 3500/4000/5000	2 2 ft				F2 ² 3/8" flex, 18 ga. 6'; 4 leads (2 hots, neutral, ground) does not include dimming leads
2DSRT	4060L 3800/4800/5500	CS 3500/4000/5000	4 4 ft				F2/5W ¹ 3/8" single flex, 18 ga. 6' for dimmable luminaires; 5 leads (hot, neutral, ground, Dim+/Dim-) F2/6W ² 3/8" single flex, 18 ga. 6' for dimmable & EM fixtures; 6 leads (2 hot, neutral, ground, Dim+/Dim-)
							EM10RM Bodine BSL310 10W battery pack w/remote test switch
							DAYOCC Basic occupancy and daylight sensing

Engineering table

Catalog Code	Size	Voltage	Power / Wattage			Lumens ³			Efficacy		
			3500K	4000K	5000K	3500K	4000K	5000K	3500K	4000K	5000K
1DSRT3050LCS-4-UNV-DIM	1x4	UNV	39	39	39	5000	5150	5000	128	132	128
1DSRT3050LCS-4-UNV-DIM	1x4	UNV	31	31	31	4000	4100	4000	129	132	129
1DSRT3050LCS-4-UNV-DIM	1x4	UNV	23	23	23	2850	2900	2900	124	126	126
2DSRT3050LCS-2-UNV-DIM	2x2	UNV	35	35	35	4350	4500	4400	124	129	126
2DSRT3050LCS-2-UNV-DIM	2x2	UNV	28	28	28	3650	3800	3700	130	136	132
2DSRT3050LCS-2-UNV-DIM	2x2	UNV	22	22	22	2750	2750	2800	125	125	127
2DSRT4060LCS-4-UNV-DIM	2x4	UNV	46	46	46	6000	6150	6100	130	134	133
2DSRT4060LCS-4-UNV-DIM	2x4	UNV	39	39	39	5000	5150	5000	128	132	128
2DSRT4060LCS-4-UNV-DIM	2x4	UNV	30	30	30	4000	4100	4000	133	137	133

1. Not available with EM10RM.
2. The F2 and F2/6W are only available with EM10RM.
3. Nominal delivered lumens at 25°C ambient.
4. The DSRT-EM-Harness must be ordered with FPEMLED.
5. Not compatible with emergency battery packs.



Visit signify.com/warranties for more information on Signify's standard 5-year limited warranty.

Accessories (order separately)

- FPEMLED10RM⁴ - 10W Emergency Driver Kit (field assembled)
- DSRT-EM-HARNESS⁴ - conversion harness for use with FPEMLED10RM
- DSRT-CKT-NP⁵ - Selectable Troffer Suspension Kit with no Power
- DSRT-CKT-WP⁵ - Selectable Troffer Suspension Kit with Power
- 1DSRT-4-SKT⁵ - 1x4' Selectable Troffer Surface Kit
- 2DSRT-2-SKT⁵ - 2x2' Selectable Troffer Surface Kit
- 2DSRT-4-SKT⁵ - 2x4' Selectable Troffer Surface Kit
- FMA14 - 1'x4' "F" mounting frame for NEMA "F" mounting
- FMA22 - 2'x2' "F" mounting frame for NEMA "F" mounting
- FMA24 - 2'x4' "F" mounting frame for NEMA "F" mounting

Not all product variations listed on page are DLC qualified. To ensure that a specific model is qualified, visit www.designlights.org/search



© 2025 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

GENLYTE SOLUTIONS
a signify business

Signify North America Corp.
400 Crossing Blvd, Suite 600
Bridgewater, NJ 08807
Telephone: 800-555-0050

Signify Canada Ltd.
281 Hillmount Road,
Markham, ON, Canada L6C 2S3
Telephone: 800-668-9008

All trademarks are owned by Signify Holding or their respective owners.