



PHILIPS

LED lamps

Warm glow effect


The more you dim, **the warmer the light**

Philips LED bulbs with a warm glow dimming effect dim just like traditional incandescent bulbs – not all LEDs dim the same. These LED bulbs get warmer in tone as the light dims. Other LED bulbs simply get less bright, without the cozy glow. This warm glow effect technology is offered in many shapes and wattages in our bulb, spot, candle and decorative lamp categories. Some of the clear lamps feature a new omni-directional prism that creates the look and feel of a filament, with a uniform lighting effect for use in most lighting fixtures.

Philips LED lamps with warm glow effect



Product No. (6nc)	Model No. (12nc)	Description	Base	Watts (W)	Lumens (lm)	Volts (V)	CRI (min)	CCT (K)	Lifetime ¹ (hrs)	Material	Finish	Legend	
A19 40W lamp equivalent dimming													
W ■	549485	929001969504	5A19/PER/927-922/CL/G/E26/WGX 1FB T20	A19	5	450	120	90	15,000	2700-2200	Glass	Clear	A
D ■ E ■	479428	929001940704	5A19/PER/927-22/P/E26/WG 6/1FB T20	A19	5	450	120	90	15,000	2700-2200	Plastic	Frosted	B
A19 60W lamp equivalent dimming													
W ■ E ■	573436	929003083243	8A19/PER/UD/FR/G/E26/WGD 4/2PFT20	A19	8	800	120	95	15,000	2700-2200	Glass	Frosted	C
W ■	549493	929001969604	8A19/PER/927-922/CL/G/E26/WGX 1FB T20	A19	8	800	120	90	15,000	2700-2200	Glass	Clear	D
D ■ E ■	479444	929001940904	8.8A19/PER/927-22/P/E26/WG 6/1FB T20	A19	8.8	800	120	90	25,000	2700-2200	Plastic	Frosted	B
A19 75W lamp equivalent dimming													
D ■ E ■	561000	929002285404	12.2A19/PER/927-22/P/E26/WG 6/1FB T20	A19	12.2	1100	120	90	15,000	2200 - 2700	Plastic	Frosted	E
A19 100W lamp equivalent dimming													
D ■ E ■	561027	929002285504	16A19/PER/927-22/P/E26/WG 6/1FB T20	A19	16	1600	120	90	15,000	2200-2700	Plastic	Frosted	E
A19 150W lamp equivalent dimming													
D ■	571497	929002343033	29A21/PER/827/FR/P/E26/WG/HO 4/1PF	A21	29	2610	120	80	15,000	2200-2700	Plastic	Frosted	E
R20 45W equivalent lamps dimming													
D ■ E ■	456979	929002008904	5R20/PER/927-22/P/E26/WG 6/1FB T20	R20	5	450	120	90	15000	2700-2200	Plastic	Frosted	F
BR30 65W equivalent lamps dimming													
D ■ E ■	457044	929001870334	7.2BR30/PER/922-27/P/E26/WG 6/1FB T20	BR30	7.2	650	120	90	15000	2700-2200	Plastic	Frosted	G
BR30 100W equivalent lamps dimming													
D ■ E ■	571471	929002351433	15BR30/PER/927/P/E26/WG/HO/T20 4/1PF	BR30	15	1400	120	90	15000	2700-2200	Plastic	Frosted	G
BR45 85W equivalent lamps dimming													
D ■ E ■	577841	929003477104	13.3BR40/PER/927-22/P/E26/WG 6/1CT T20	BR40	13.3	1204	120	90	15000	2700-2200	Plastic	Frosted	H
BR45 150W equivalent lamps dimming													
D ■ E ■	558049	929002351203	20BR40/PER/927-22/E26/WG/HO 4/1FB T20	BR40	20	2175	120	90	15000	2700-2200	Plastic	Frosted	I



Product No. (6nc)	Model No. (12nc)	Description	Base	Watts (W)	Lumens (lm)	Volts (V)	CRI (min)	CCT (K)	Lifetime ¹ (hrs)	Base	Material	Finish	Legend	
MR16 35W equivalent lamps dimming														
D ■ E ■	574400	929003087104	6.5MR16/F25/2700-2200 DIM 12V	MR16	6.5	410	12	80	25,000	2700-2200	GU5.3	1800	25	A
D ■ E ■	574418	929003087204	6.5MR16/F35/2700-2200 DIM 12V	MR16	6.5	455	12	80	25,000	2700-2200	GU5.3	950	35	A
GU10 50W equivalent lamps dimming														
D ■ E ■	471565	929002055304	4GU10/LED/927-22/F35/G/WG/T20 10/1	GU10	4	380	120	90	25,000	2700-2200	GU10	600	35	B
PAR20 50W equivalent lamps dimming														
D ■ E ■	568105	929003026304	5.5PAR20/LED/F25/927-922/G/DIM/T20 6/1FB	PAR20	5.5	500	120	90	25,000	2700-2200	E26	1300	25	C
D ■ E ■	568113	929003026704	5.5PAR20/LED/F40/927-922/DIM/G/T20 6/1FB	PAR20	5.5	500	120	90	25,000	2700-2200	E26	800	40	C

1. Tested to B50 L70 requirement. LED lifetime means the length of time (in hours) until half of the LED light sources maintain at least 70% of their initial lumen output (B50, L70). Lamps rated 15,000 hours is in an enclosed fixture. Life rating is 25,000 in an unenclosed. Warranty is based off of 15,000 hour claim.

2. MC/CP/CNG = MasterClass, CorePro or Contractor Grade.

D = Damp loc. W = Wet loc. E = Enclosed suitable ■ = Title 24 (JA8) compliant ■ = Title 20 compliant ■ = Not regulated by Title 20

Philips LED lamps with warm glow effect



Product No. (6nc)	Model No. (12nc)	Description	Watts Base (W)	Lumens (lm)	Volts (V)	CRI (min)	CCT (K)	Lifetime ¹ (hrs)	Base	Material	Finish	Legend		
A15 40W equivalent lamps dimming														
W ■	549386	929002208304	3.8A15/PER/927-922/CL/G/E26/WGX1FB T20	A15	3.8	350	120	90	15,000	2700-2200	E26	Glass	Clear	A
A15 60W equivalent lamps dimming														
W ■	549394	929002208404	5.5A15/PER/927-922/CL/G/E12/WGX1FB T20	A15	5.5	500	120	90	15,000	2700-2200	E12	Glass	Clear	B
W ■	564450	929002986803	5A15/PER/UD/CL/G/E12/WGD 6/2PF T20	A15	5	450	120	95	15,000	2700-2200	E12	Glass	Clear	C
W ■	549402	929002208604	5.5A15/PER/927-922/CL/G/E26/WGX1FB T20	A15	5.5	500	120	90	15,000	2700-2200	E26	Glass	Clear	A
W ■	564385	929002986503	5A15/PER/UD/CL/G/E26/WGD 6/2PF T20	A15	5	450	120	95	15,000	2700-2200	E26	Glass	Clear	D
Candles 25W equivalent lamps dimming														
W ■	566653	929002991803	2.3BA11/PER/UD/CL/G/E12/WGD 6/3PFT20	BA11	2.3	185	120	95	15,000	2700-2200	E12	Glass	Clear	E
Candles 40W equivalent lamps dimming														
W ■	549568	929001969404	3.3B11/PER/927-922/CL/G/E12/WGX 1FB T20	B11	3.3	300	120	90	15,000	2700-2200	E12	Glass	Clear	F
W ■	549584	929002047204	3.3B11/PER/927-922/CL/G/E26/WGX1FB T20	B11	3.3	300	120	90	15,000	2700-2200	E26	Glass	Clear	G
W ■	574392	929003089903	3.5B11/PER/UD/CL/G/E26/WGD 6/3PF T20	B11	3.5	300	120	95	15,000	2700-2200	E26	Glass	Clear	H
W ■	549543	929001969204	3.3BA11/PER/927-922/CL/G/E12/WGX 1FB T20	BA11	3.3	300	120	90	15,000	2700-2200	E12	Glass	Clear	I
W ■	566661	929002990703	3.5BA11/PER/UD/CL/G/E12/WGD 6/3PF T20	BA11	3.5	300	120	95	15,000	2700-2200	E12	Glass	Clear	E
W ■	566679	929002991703	3.5BA11/PER/UD/CL/G/E26/WGD 6/3PF T20	BA11	3.5	300	120	95	15,000	2700-2200	E12	Glass	Clear	J
Candles 60W equivalent lamps dimming														
W ■	549337	929002204504	5.5B11/PER/927-922/CL/G/E12/WGX 1FB T20	B11	5.5	500	120	90	15,000	2700-2200	E12	Glass	Clear	F
W ■	573378	929003085503	5B11/PER/UD/CL/G/E26/WGD 6/3PF T20	B11	5	500	120	95	15,000	2700-2200	E26	Glass	Clear	K
W ■	566687	929002991003	5BA11/PER/UD/CL/G/E12/WGD 6/3PF T20	BA11	5	500	120	95	15,000	2700-2200	E12	Glass	Clear	L
W ■	566695	929002991103	5BA11/PER/UD/CL/G/E26/WGD 6/3PF T20	BA11	5	500	120	95	15,000	2700-2000	E26	Glass	Clear	M
W ■	575167	929002990804	5BA11/PER/CRI95WG/FR/G/E12/WGD 1CT	BA11	5	500	120	95	15000	2700-2200	E12	Glass	Frosted	N
W ■	575183	929003082404	5BA11/PER/CRI95WG/FR/G/E26/WGD 1CT	BA11	5	500	120	95	15000	2700-2200	E26	Glass	Frosted	O
W ■	575191	929003082504	5B11/PER/CRI95WG/FR/G/E12/WGD 1CT	B11	5	500	120	95	15000	2700-2200	E12	Glass	Frosted	P
W ■	575175	929003094904	5B11/PER/CRI95WG/FR/G/E26/WGD 1CT	B11	5	500	120	95	15000	2700-2200	E26	Glass	Frosted	Q
W ■	547959	929002091503	5.5F15/PER/927-922/CL/G/E26/WGX 1BC	F15	5.5	500	120	90	15,000	2700-2200	E26	Glass	Clear	R
W ■	572669	929002091593	5.5F15/PER/927-922/CL/G/E26/WGX 1PF T20	F15	5.5	500	120	90	15,000	2700-2200	E26	Glass	Clear	R
Candles 75W equivalent lamps dimming														
W ■	564492	929002986603	6.6/BA11/PER/UD/CL/G/E12+E26/WGD 3PF T20	BA11	6.6	700	120	95	15,000	2700-2200	E12/E26	Glass	Clear	S

Philips LED lamps with warm glow effect



Product No. (6nc)	Model No. (12nc)	Description	Base	Watts (W)	Lumens (lm)	Volts (V)	CRI (min)	CCT (K)	Lifetime ¹ (hrs)	Base	Material	Finish	Legend	
G16.5 25W equivalent lamps dimming														
W ■	549253	929002204804	2.7G16.5/PER/927-922/CL/G/E26/WGX1FBT20	G16.5	2.7	250	120	90	15,000	2700-2200	E26	Glass	Clear	A
W ■	549261	929002204904	2.7G16.5/PER/927-922/CL/G/E12/WGX1FBT20	G16.5	2.7	250	120	90	15,000	2700-2200	E12	Glass	Clear	B
G16.5 40W equivalent lamps dimming														
W ■	549287	929002205104	3.8G16.5/PER/927-922/CL/G/E12/WGX1FBT20	G16.5	3.8	350	120	90	15,000	2700-2200	E12	Glass	Clear	C
W ■	573303	929003085203	3.5G16.5/PER/UD/CL/G/E12/WGD6/2PFT20	G16.5	3.5	350	120	95	15,000	2700-2200	E12	Glass	Clear	D
W ■	549279	929002205004	3.8G16.5/PER/927-922/CL/G/E26/WGX1FBT20	G16.5	3.8	350	120	90	15,000	2700-2200	E26	Glass	Clear	E
W ■	573295	929003085103	3.5G16.5/PER/UD/CL/G/E26/WGD6/2PFT20	G16.5	3.5	350	120	95	15,000	2700-2200	E26	Glass	Clear	F
W ■	564591	929002205423	3.8G16.5/PER/927-922/FRGE26/WGX2PFT20	G16.5	3.8	350	120	90	15,000	2700-2200	E26	Glass	Frosted	G
G16.5 60W equivalent lamps dimming														
W ■	549303	929002205304	5.5G16.5/PER/927-922/CL/G/E12/WGX1FBT20	G16.5	5.5	500	120	90	15,000	2700-2200	E12	Glass	Clear	C
W ■	573329	929003085403	5G16.5/PE/UD/CL/G/E12/WGD6/2PFT20	G16.5	5	500	120	95	15,000	2700-2200	E12	Glass	Clear	H
W ■	549295	929002205204	5.5G16.5/PER/927-922/CL/G/E26/WGX1FBT20	G16.5	5.5	500	120	90	15,000	2700-2200	E26	Glass	Clear	E
W ■	573311	929003085303	5G16.5/PER/UD/CL/G/E26/WGD6/2PFT20	G16.5	5	500	120	95	15,000	2700-2200	E26	Glass	Clear	I
G25 25W equivalent lamps dimming														
W ■	572255	929002208099	2.7G25/PER/927-922/FR/G/E26/WGX4/2PFT20	G25	2.7	250	120	95	15,000	2700-2200	E26	Glass	Frosted	J
G25 40W equivalent lamps dimming														
W ■	573352	929003085003	3.5G25/PER/UD/FR/G/E26/WGD4/2PFT20	G25	3.5	350	120	95	15,000	2700-2200	E26	Glass	Frosted	J
G25 60W equivalent lamps dimming														
W ■	549519	929001969804	5.5G25/PER/927-922/CL/G/E26/WGX1FB T20	G25	5.5	500	120	90	15,000	2700-2200	E26	Glass	Clear	M
W ■	549535	929001970004	5.5G25/PER/927-922/FR/G/E26/WGX1FB T20	G25	5.5	500	120	90	15,000	2700-2200	E26	Glass	Frosted	J

1. Tested to B50 L70 requirement. LED lifetime means the length of time (in hours) until half of the LED light sources maintain at least 70% of their initial lumen output (B50, L70). Lamps rated 15,000 hours is in an enclosed fixture. Life rating is 25,000 in an unenclosed. Warranty is based off of 15,000 hour claim.

2. MC/CP/CNG = MasterClass, CorePro or Contractor Grade.

■ = Damp loc. ■ = Wet loc. ■ = Enclosed suitable ■ = Title 24 (JAB) compliant ■ = Title 20 compliant ■ = Not regulated by Title 20



© 2024 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.



Signify North America Corporation
400 Crossing Boulevard,
Bridgewater, NJ 08807
Telephone 800-555-0050

Signify Canada Ltd.
281 Hillmount Road,
Markham, ON, Canada L6C 2S3
Telephone 800-668-9008

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.