

# PHILIPS

## LED lamps

### InstantFit PL lamps



# This is real **compatibility**

**Philips InstantFit LED lamps** make the transition to LED from CFL lamps as simple as replacing a lamp. With both vertical and horizontal options and a wide array of color temperatures, the InstantFit LED lamps can quickly and effectively replace compact fluorescent lamps. The horizontal version includes a rotatable end cap to ensure the light is correctly aimed.

## Benefits

- **Proven over 40% energy savings<sup>1</sup>**  
Over fluorescent means a satisfied customer and no time wasted going back to a job
- **Lifetime delivered**  
Average life rating of 50,000 hours<sup>2</sup>
- **Easy replacement of conventional:**  
32W & 26W 4-pin (PL-C & PL-T) lamps  
13W 2-pin & 4-pin (PL-S & PL-C) lamps  
40W 4-pin (PL-L) lamps

## Features

- **Rotatable end cap**  
Ensures proper lamp alignment inside the fixture (horizontal SKUs only)
- **Long life**  
Less maintenance than CFL with 50,000 hour life<sup>2</sup>
- **Proven product history**  
A company with a long history of innovation and reliability in the lighting industry
- **Dimmable**  
Many Philips LED PL-type lamps are dimmable

# Philips InstantFit PL lamps



Ordering, electrical and technical data (Subject to change without notice)

Product No. (6nc)	Model No. (12nc)	DLC Product ID	Description	Bare System Equiv.				Base	Volts (V)	CRI (min)	CCT (K)	Lifetime <sup>1</sup> (hrs)	Beam Angle	Lgd
				Watts (W)	Watts (W)	Watts (W)	Lumens (lm)							
<b>CorePro - 2-pin PL-S Type A (Ballast Compatible)</b>														
529511	929001862804	N/A	5PL-S/LED/13H/827/IF5/P/2P 20/1	5	5	13	580	GX23	120-277	82	2700	50,000	180°	A
529578	929001863004	N/A	5PL-S/LED/13H/835/IF5/P/2P 20/1	5	5	13	580	GX23	120-277	82	3500	50,000	180°	A
529586	929001863104	N/A	5PL-S/LED/13H/840/IF5/P/2P 20/1	5	5	13	580	GX23	120-277	82	4000	50,000	180°	A
<b>CorePro - 2-pin PL-C Type A (Ballast Compatible)</b>														
532341	929001884804	N/A	5PL-C/LED/13H/840/IF5/P/2P 20/1	5	5	13	580	GX23-2	120-277	82	4000	50,000	150°	B
<b>CorePro - 4-pin PL-C Type A (Ballast Compatible)</b>														
532408	929001885404	-	5.5PL-C/LED/13H/830/IF5.5/P/4P 20/1	5.5	7	13	550	G24q	14-60	82	3000	50,000	150°	D
532416	929001885504	-	5.5PL-C/LED/13H/835/IF5.5/P/4P 20/1	5.5	7	13	580	G24q	14-60	82	3500	50,000	150°	D
532424	929001885604	-	5.5PL-C/LED/13H/840/IF5.5/P/4P 20/1	5.5	7	13	580	G24q	14-60	82	4000	50,000	150°	D
532432	929001885704	-	5.5PL-C/LED/13V/827/IF5.5/P/4P 20/1	5.5	7	13	550	G24q	14-60	82	2700	50,000	150°	E
<b>CorePro - 4-pin PL-C/T Type A (Ballast Compatible)</b>														
458364	929001388004	P227UKPG	8.5PL-C/T LED/26H-2700 IF 4P 10/1	8.5	10.5	26	900	G24q	100-277, 347	82	2700	50,000	120°	F
458372	929001388104	PYHS75V7	8.5PL-C/T LED/26H-3000 IF 4P 10/1	8.5	10.5	26	900	G24q	100-277, 347	82	3000	50,000	120°	F
458380	929001388204	P1956NU5	8.5PL-C/T LED/26H-3500 IF 4P 10/1	8.5	10.5	26	900	G24q	100-277, 347	82	3500	50,000	120°	F
458398	929001388304	PUK7J4AA	8.5PL-C/T LED/26H-4000 IF 4P 10/1	8.5	10.5	26	950	G24q	100-277, 347	82	4000	50,000	120°	F
458406	929001181104	PW2GPMX6	10.5PL-C/T LED/26V-2700 IF 4P 10/1	10.5	14.5	26	1200	G24q	100-277, 347	82	2700	50,000	120°	G
458414	929001181204	PGPTBMF9	10.5PL-C/T LED/26V-3000 IF 4P 10/1	10.5	14.5	26	1200	G24q	100-277, 347	82	3000	50,000	120°	G
458422	929001181304	PZIKRNR	10.5PL-C/T LED/26V-3500 IF 4P 10/1	10.5	14.5	26	1200	G24q	100-277, 347	82	3500	50,000	120°	G
458430	929001181404	PV2HQGWZ	10.5PL-C/T LED/26V-4000 IF 4P 10/1	10.5	14.5	26	1300	G24q	100-277, 347	82	4000	50,000	120°	G
<b>InstantFit LED - 4-pin dimmable (32W replacements)</b>														
476077	929001819804	PO8NB9Q1	12PL-C/T/COR/32H-830/IF13/P/4P/DIM 10/1	12	15	32	1350	G24/GX24	100-277, 347	82	3000	50,000	120°	F
476085	929001819904	PZHFI5JO	12PL-C/T/COR/32H-835/IF14/P/4P/DIM 10/1	12	15	32	1400	G24/GX24	100-277, 347	82	3500	50,000	120°	F
476093	929001820004	PT5IC4ON	12PL-C/T/COR/32H-840/IF14/P/4P/DIM 10/1	12	15	32	1450	G24/GX24	100-277, 347	82	4000	50,000	120°	F
476119	929001820204	PEIZQ8AS	12PL-C/T/COR/32V-830/IF14/P/4P/DIM 10/1	12	15	32	1400	G24/GX24	100-277, 347	82	3000	50,000	120°	G
476127	929001820304	PJG8ADHK	12PL-C/T/COR/32V-835/IF14/P/4P/DIM 10/1	12	15	32	1450	G24/GX24	100-277, 347	82	3500	50,000	120°	G
476135	929001820404	PFKH6AQ	12PL-C/T/COR/32V-840/IF15/P/4P/DIM 10/1	12	15	32	1500	G24/GX24	100-277, 347	82	4000	50,000	120°	G
<b>CorePro - 2-pin PL-S Type A (Ballast Compatible)</b>														
532895	929001893504	P31FZ6G6	16.5PL-L/PER/22/830/IF22/P 4P 10/1	16.5	21	40	2200	2G11	100-277, 347	82	3000	50,000	160°	A
532903	929001893604	PAVW5BH3	16.5PL-L/PER/22/835/IF22/P 4P 10/1	16.5	21	40	2200	2G11	100-277, 347	82	3500	50,000	160°	A
532911	929001893704	PIWSEVIM	16.5PL-L/PER/22/840/IF23/P 4P 10/1	16.5	21	40	2300	2G11	100-277, 347	82	4000	50,000	160°	A

1. Lamps rated 15,000 hours is in an enclosed fixture. Life rating is 25,000 in an unenclosed. Warranty is based off of 15,000 hour claim.  
Lamps rated at 25,000 hours is for an unenclosed fixture. Life rating is 15,000 hours for enclosed. Warranty is based off of 25,000 hour claim.  
Note: Highlighted items are available only while supplies last.



© 2020 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.



Signify North America Corporation  
200 Franklin Square Drive,  
Somerset, NJ 08873  
Telephone 855-486-2216

Signify Canada Ltd.  
281 Hillmount Road,  
Markham, ON, Canada L6C 2S3  
Telephone 800-668-9008

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.