

PHILIPS

LED lamps

MainsFit (UL Type-B)



Installation **simplified**

Philips LED MainsFit (UL Type B) T8 lamps use a double-ended design which significantly simplifies installation, saving time and costs. This product can replace T5, T8, T12 or PL-L lamps in fixtures containing shunted or non-shunted sockets.¹

Benefits

- **Easy install**
All Philips MainsFit lamps are double-ended for faster installs
- **Installation simplicity**
Can be used with both shunted and non-shunted sockets
- **Maximum durability**
Available in plastic for the best anti-shatter performance
- **Emergency Capable**
Compatible with the new PTB15D emergency driver or the Bodine ELI-S series emergency inverters²
- **Light quality and performance predictability**
Consistent light output and no flicker means delighted customers

Features

- **Ballast bypass**
UL Type B (120-277V)
- **Lifetime delivered**
Up to 70,000 hr average life rating³
- **Available sizes**
T8: 1ft, 4ft, & 8ft
T5: 4ft (HO), 4ft (HE), 3ft (HE), 2ft (HE) & 1ft (HE)
PLED: PL-S, PL-C/T and PL-L
- **Energy Savings**
Proven over 40% energy savings over fluorescent systems⁴
- **Wide beam light distribution**
Up to 240° beam angle, 350° illumination angle⁵
- **DLC certified**
All MainsFit lamps are DLC listed⁶

1. For proper operation shunting of un-shunted sockets is required. See installation instructions for details.
2. PTB15D compatible only with 4ft T8 MainsFit lamps. For other MainsFit lamps please use Bodine ELI-S series of emergency inverters.

3. LED lifetime means the length of time (in hours) until half of the LED light sources maintain at least 70% of their initial lumen output (B50, L70).
4. Savings based on comparison to F32T8 electronic instant start systems.
5. Photometric testing consistent with IES LM-79.
6. DLC listed where DLC categories exist.

Philips LED MainsFit lamps (UL Type B)



Ordering, electrical and technical data (Subject to change without notice)



Product No. (6nc)	Model No. (12nc)	DLC Product ID	Description	Watts (W)	Lumens (lm)	CRI (min)	CCT (K)	Lifetime ¹ (hrs)	Beam Angle	MOL (in)	Materials	Pkg Qty
MasterClass (Plastic) MainsFit (Type B) - T8 4ft (120-277V)												
579441	929003525104	S-573ND4	10.5T8/MAS/48-835/MF15/P/DIM 25/1	11	1550	82	3500	70,000	180	48	Plastic	25
579458	929003525204	S-QI8DGT	10.5T8/MAS/48-840/MF16/P/DIM 25/1	11	1600	82	4000	70,000	180	48	Plastic	25
579466	929003525304	S-7KSJBW	10.5T8/MAS/48-850/MF16/P/DIM 25/1	11	1600	82	5000	70,000	180	48	Plastic	25
579516	929003525804	S-A8FD2T	16.5T8/MAS/48-835/MF24/P/DIM 25/1	17	2500	82	4000	70,000	180	48	Plastic	25
579524	929003525904	S-B2KA75	16.5T8/MAS/48-840/MF25/P/DIM 25/1	17	2450	82	3500	70,000	180	48	Plastic	25
579532	929003526004	S-809PNW	16.5T8/MAS/48-850/MF25/P/DIM 25/1	17	2500	82	5000	70,000	180	48	Plastic	25
CorePro MainsFit (Type B) - T8 1.5ft (120-277V)												
592758	929004244604	No Category	7T8/COR/18-5CCT/MF9/G 25/1	7	900	82	3000/3500/4000/5000/6500	50,000	250	18	Glass	25
CorePro MainsFit (Type B) - T8 4ft (120-277V)												
579318	929003523704	S-RCNBD2	9.9T8/COR/48-835/MF15/G/DIM 25/1	10	1500	80	3500	50,000	240	48	Glass	25
579326	929003523804	S-4GP25S	9.9T8/COR/48-840/MF16/G/DIM 25/1	10	1650	80	4000	50,000	240	48	Glass	25
579334	929003523904	S-Q9GJNX	9.9T8/COR/48-850/MF16/G/DIM 25/1	10	1650	80	5000	50,000	240	48	Glass	25
579342	929003524104	S-J0O65Y	12T8/COR/48-830/MF17/G/DIM 25/1	12	1700	80	3000	50,000	240	48	Glass	25
579359	929003524204	S-6OHQAZ	12T8/COR/48-835/MF17/G/DIM 25/1	12	1700	80	3500	50,000	240	48	Glass	25
579383	929003524304	S-YDPVZ5	12T8/COR/48-840/MF18/G/DIM 25/1	12	1800	80	4000	50,000	240	48	Glass	25
579391	929003524404	S-E47N92	12T8/COR/48-850/MF18/G/DIM 25/1	12	1800	80	5000	50,000	240	48	Glass	25
579409	929003524604	S-VCHIM9Y	14.5T8/COR/48-830/MF20/G/DIM 25/1	15	2000	80	3000	50,000	240	48	Glass	25
579417	929003524704	S-4AS9KG	14.5T8/COR/48-835/MF20/G/DIM 25/1	15	2000	80	3500	50,000	240	48	Glass	25
579425	929003524804	S-Z5VAIG	14.5T8/COR/48-840/MF21/G/DIM 25/1	15	2100	80	4000	50,000	240	48	Glass	25
579433	929003524904	S-N68XAH	14.5T8/COR/48-850/MF21/G/DIM 25/1	15	2100	80	5000	50,000	240	48	Glass	25
Contractor-grade MainsFit (Type B) - T8 4ft (120-277V)												
610279	929004351104	S-MDRWDB	13.4T8/CNG/48-835/MX17/G 25/1	13.4	1750	80	3500	50,000	240	48	Glass	25
610287	929004351204	S-2D39WD	13.4T8/CNG/48-840/MX18/G 25/1	13.4	1800	80	4000	50,000	240	48	Glass	25
610295	929004351304	S-GHIM99	13.4T8/CNG/48-850/MX18/G 25/1	13.4	1800	80	5000	50,000	240	48	Glass	25
610300	929004351404	S-SV2BCS	13.4T8/CNG/48-865/MX18/G 25/1	13.4	1800	80	6500	50,000	240	48	Glass	25
610310	929004351504	S-2VW3K5	15.3T8/CNG/48-835/MX20/G 25/1	15.3	2050	80	3500	50,000	240	48	Glass	25
610329	929004351604	S-9DDN7P	15.3T8/CNG/48-840/MX21/G 25/1	15.3	2100	80	4000	50,000	240	48	Glass	25
610337	929004351704	S-Z2CXQD	15.3T8/CNG/48-850/MX21/G 25/1	15.3	2100	80	5000	50,000	240	48	Glass	25
CorePro MainsFit (Type B) - T8 8ft (120-277V)												
589804	929003815504	PNV8L83H	40T8/COR/96-5CCT/MF55LS/G/FA8-R17D 10/1	26/34/40	3400/4300/5500	82	3000/3500/4000/5000/6500	50,000	240	96	Glass	10
Ultra Efficient MasterClass Glass (Type B) - T8 (120-277V)												
610246	929004319204	S-MGRN33	8.4T8/MAS/48-835/MF15/G/DIM UE 25/1	8.4	1550	80	3500	50,000	240	48	Glass	25
610250	929004319304	S-86559Y	8.4T8/MAS/48-840/MF16/G/DIM UE 25/1	8.4	1600	80	4000	50,000	240	48	Glass	25
610260	929004319404	S-NTQVBG	8.4T8/MAS/48-850/MF16/G/DIM UE 25/1	8.4	1600	80	5000	50,000	240	48	Glass	25
CorePro MainsFit (Type B) - T5 1ft (120-277V)												
592766	929004235004	No Category	4.5T5HE/COR/12-5CCT/MF5/G 25/1	4.5	500	82	3000/3500/4000/5000/6500	50,000	250	12	Glass	25
CorePro MainsFit (Type B) - T5 2ft (120-277V)												
592774	929004235104	No Category	9T5HE/COR/22-5CCT/MF12/G 25/1	9	1200	82	3000/3500/4000/5000/6500	50,000	250	22	Glass	25
CorePro MainsFit (Type B) - T5 3ft (120-277V)												
592782	929004235204	No Category	12T5HE/COR/34-5CCT/MF16/G 25/1	12	1600	82	3000/3500/4000/5000/6500	50,000	250	34	Glass	25

Philips LED MainsFit (UL Type B) lamps



G5 G13 G23

GX23 G24q 2G11

Ordering, electrical and technical data (Subject to change without notice)

Product No. (6nc)	Model No. (12nc)	DLC Product ID	Description	Watts (W)	Lumens (lm)	CRI (min)	CCT (K)	Lifetime ¹ (hrs)	Beam Angle	MOL (in)	Materials	Pkg Qty
CorePro MainsFit (Type B) - T5 4ft (120-277V)												
592790	929004235304	No Category	13T5HE/COR/46-5CCT/MF18/G 25/1	13	1800	82	3000/3500/4000/5000/6500	50,000	250	46	Glass	25
576231	929003122404	PY2MWDXX	25T5HO/COR/46-835/MF33/G 25/1	25	3300	80	3500	50,000	200	46	Glass	25
576249	929003122504	POSBWIPB	25T5HO/COR/46-840/MF35/G 25/1	25	3500	82	4000	50,000	200	46	Glass	25
576256	929003122604	PKPRHYIX	25T5HO/COR/46-850/MF35/G 25/1	25	3500	82	5000	50,000	200	46	Glass	25
CorePro PL-L (Type B) ballast bypass - 4-pin (120-277V)												
575100	929003097504	PMRRH3FX	17PL-L/COR/22-830/MF22/G/4P 10/1	17	2200	82	3000	50,000	240	22	Glass	10
575118	929003097604	PDOC47TH	17PL-L/COR/22-835/MF22/G/4P 10/1	17	2200	82	3500	50,000	240	22	Glass	10
575126	929003097704	PE7ZEGUJ	17PL-L/COR/22-840/MF22/G/4P 10/1	17	2200	82	4000	50,000	240	22	Glass	10
CorePro PL-L Color Adjustable (Type B) ballast bypass - 4-pin (120-277V)												
607127	929004602404	No Category	8PL-L/COR/18-5CCT/MF9/G/4P 10/1	8	900/900/900/950/950	82	2700/3000/3500/4000/5000	50,000	140	9	Plastic	10
607135	929004602504	No Category	10PL-L/COR/24-5CCT/MF11/G/4P 10/1	10	1100/1100/1100/1150/1150	82	2700/3000/3500/4000/5000	50,000	140	13	Plastic	10
607143	929004602604	No Category	16PL-L/COR/36-5CCT/MF20/G/4P 10/1	16	1900/1900/1900/2000/2000	82	2700/3000/3500/4000/5000	50,000	140	16	Plastic	10
607150	929004602704	No Category	18PL-L/COR/55-5CCT/MF28/G/4P 10/1	18	2550/2550/2550/2800/2800	82	2700/3000/3500/4000/5000	50,000	140	21	Plastic	10
CorePro PL-C/T Color Adjustable (Type B) ballast bypass - 4-pin (120-277V)												
577890	929003477604	No Category	8PL-C/T/COR/26H-3CCT/MF10/P/20/1	8	975/1000/1050	>80	3000/3500/4000	30,000	120	6	Plastic	20
577908	929003477704	No Category	8PL-C/T/COR/26V-3CCT/MF10/P/20/1	8	975/1000/1050	>80	3000/3500/4000	30,000	120	5	Plastic	20
577916	929003477804	No Category	11PL-C/T/COR/32H-3CCT/MF15/P/20/1	11	1425/1450/1500	>80	3000/3500/4000	30,000	120	6	Plastic	20
577924	929003477904	No Category	11PL-C/T/COR/32V-3CCT/MF15/P/20/1	11	1425/1450/1500	>80	3000/3500/4000	30,000	120	5	Plastic	20
CorePro PL-S Color Adjustable (Type B) ballast bypass - 4-pin (120-277V)												
606566	929004582904	No Category	5PL-S/COR/9H-5CCT/MF5/P/2P 20/1	5	475/475/475/500/500	82	2700/3000/3500/4000/5000	50,000	140	7	Plastic	20
606574	929004583004	No Category	6PL-S/COR/13H-5CCT/MF6/P/2P 20/1	6	620/620/620/650/650	82	2700/3000/3500/4000/5000	50,000	140	7	Plastic	20



For more information on Philips' limited warranty please visit genlyte.com/en-us/support/warranties



© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Signify North America Corp.
400 Crossing Blvd, Suite 600
Bridgewater, NJ 08807
Telephone: 800-555-0050

All trademarks are owned by Signify Holding or their respective owners.

GENLYTE
SOLUTIONS

a Signify business