

PHILIPS

LED lamps

MainsFit CorePro
PLL-PLS (UL Type-B)



Select your color

Philips PLED MainsFit PLL & PLS (Type B) color selectable lamps feature a switch to select between 5 different CCTs from 2700K to 5000K. Unsure of the color that will fit your application best? No need to worry with Philips PLED MainsFit (Type B) color selectable lamps offering superior color consistency and color accuracy.

Benefits

- **One lamp, 5 colors**
Use the switch to select from 2700K, 3000K, 3500K, 4000K or 5000K
- **Color consistency and accuracy**
Within 5 SDCM from the ANSI specification and along the back body line
- **Base Pin Solution**
4-pin PLL and 2-pin PLS base
- **Double-ended Type B**
Eliminate the ballast with simple installation using shunted or non-shunted sockets¹
- **Lifetime Delivered**
Average life rating of 50,000 hours²

Features

- One lamp to replace five.
Reduce your inventory while providing more to your customers.
- Light quality and performance predictability offers consistent light output with no flicker
- Proven product history from a company with a long history of innovation and reliability in the lighting industry

1. For proper operation shunting of un-shunted sockets is required. See installation guide for details

2. LED lifetime means the length of time (in hours) until half of the LED light sources maintain at least 70% of their initial lumen output (B50, L70).

Philips LED MainsFit (UL Type B) lamps



Ordering, electrical and technical data (Subject to change without notice)



Product No. (6nc)	Model No. (12nc)	Description	Base	Watts (W)	Lumens (lm)	CRI (min)	CCT (K)	Lifetime ¹ (hrs)	MOL (in)	Beam	Pkg Qty
MasterClass (Plastic) MainsFit (Type B) - T8 4ft (120-277V)											
607127	929004602404	8PL-L/COR/18-5CCT/MF9/G/4P 10/1	2G11	8	900/900/900/ 950/950	82	2700/3000/3500/ 4000/5000	50,000	18	140	10
607135	929004602504	10PL-L/COR/24-5CCT/MF11/G/4P 10/1	2G11	10	1100/1100/1100/ 1150/1150	82	2700/3000/3500/ 4000/5000	50,000	24	140	10
607143	929004602604	16PL-L/COR/36-5CCT/MF20/G/4P 10/1	2G11	16	1900/1900/1900/ 2000/2000	82	2700/3000/3500/ 4000/5000	50,000	36	140	10
607150	929004602704	18PL-L/COR/55-5CCT/MF28/G/4P 10/1	2G11	18	2550/2550/2550/ 2800/2800	82	2700/3000/3500/ 4000/5000	50,000	55	140	10
606566	929004582904	5PL-S/COR/9H-5CCT/MF5/P/2P 20/1	G23	5	475/475/475/ 500/500	82	2700/3000/3500/ 4000/5000	50,000	9	140	20
606574	929004583004	6PL-S/COR/13H-5CCT/MF6/P/2P 20/1	GX23	6	620/620/620/ 650/650	82	2700/3000/3500/ 4000/5000	50,000	13	140	20

For more information on Philips' limited warranty please visit www.philips.com/warranties.



© 2025 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

PLT-2504BN 04/25 philips.com/lighting



Signify North America Corp.
400 Crossing Blvd, Suite 600
Bridgewater, NJ 08807
Telephone: 800-555-0050

Signify Canada Ltd.
281 Hillmount Road,
Markham, ON, Canada L6C 2S3
Telephone: 800-668-9008

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.