

Hadco LED Acorns and Ornamentals post top families feature a range of traditional designs, providing style and elegance to parks, downtown streets, campuses and residential communities. They also offer a range of optical distributions and options such as globes, cages, finials, FAWS, sensor ready, receptacle and shielding to customize your solution.



	Best	Best	Best	Best	Best	Best	Better	Better	Better	Better	Good	Good	Good
Category / Style	Historical Acorn	Historical Acorn	Transitional Acorn	Historical Ornamental	Historical Acorn	Historical Comfort Acorn	Historical Acorn	Historical Acorn	Historical Acorn	Transitional Ornamental	Historical Acorn	Historical Acorn	Historical Acorn
Product	Refractive Globe	Refractive Globe	Refractive Globe	New Oxford	Hagerstown	Hagerstown Comfort	MainView	Victoria Small	Victoria Large	UXI	Grosse Point	Victoria Small	Victoria Small
Prefix	RL32/RL52	RL34/RL54	CL32/CL52	VX022	TX03	TX03C	MV	VL71	VL72	UX1	3100	V71	V72
Light Engine	LumiLock GX5	LumiLock GX5	LumiLock GX5	LEDgine	LEDgine	Comfort	LumiLock GX5	EcoSwap	EcoSwap	LEDgine	LED Lamp Included	LED Lamp Included	LED Lamp Included
Lumen Output Range	Up to 18,686	Up to 18,438	Up to 16,900	Up to 14,860	Up to 19,012	Up to 8,467	Up to 17,947	Up to 7,769	Up to 7,769	Up to 14,065	Up to 6,264	Up to 7,812	Up to 7,905
Efficacy	Up to 187 LPW	Up to 184 LPW	Up to 169 LPW	Up to 128 LPW	Up to 128 LPW	Up to 102 LPW	Up to 179 LPW	Up to 121 LPW	Up to 121 LPW	Up to 114 LPW	Up to 121 LPW	Up to 151 LPW	Up to 153 LPW
Distribution	Type III Short, III Wide, V Short, V Wide	Type III Short, III Wide, V Short, V Wide	Type III Short, III Wide, V Short, V Wide	Type II, III, III Wide, IV, V	Type II, III, III Wide, IV, V	Type I, II, III, IV, V	Type III Short, V Short	Type III, V	Type III, V	Type II, III, III Wide, IV, V	Type V	Type V	Type V
Color Temperature	2700K, 3000K, 4000K	2700K, 3000K, 4000K	2700K, 3000K, 4000K	3000K, 4000K	3000K, 4000K	3000K, 4000K	2700K, 3000K, 4000K	3000K,4000K	3000K,4000K	3000K, 4000K	3000K, 4000K	3000K,4000K	3000K,4000K
Globe	Narrow Body Refractive	Wide Body Refractive	Narrow Body Refractive	Ribbed	Ribbed	Open	Visual Comfort Acorn	Acrylic	Acrylic	Open, Clear/Frosted Glass	Clear Textured	Clear, Visual Comfort	Clear, Visual Comfort
Fitter/POD	A,B,C,D,G,H,K,L,T	A,B,G,H,K,L,T	H,M,P,R	Standard	A,B,C,D,E,G,H,J,L,T	B, H	G	Standard	Standard	Standard	D, R	Standard	Standard
Roof	A,B,C,D	A,B,C,D,G	D,H,J,K with/without Brim	Standard	Standard	C,D	-	-	-	Standard	Clear, Solid	-	-
Cage/Band	A,B,E,F,H,N	B,E,F,G,I,J,N	4 Legs, 8 Legs	Standard	Standard	Q, HP	-	-	-	-	Standard	-	-
Finial	A,B,C,D,E,F,G,H,N	A,B,C,D,E,F,G,H,N	-	Standard	A,B,C,D,E,G,H,N	A,B,C,D,E,F,G,H,N	-	-	-	Standard	A,M,P,N	-	-
Mounting Height	15' - 25'	15' - 25'	15' - 25'	15' - 25'	15' - 30'	10'-15'	10'-15'	10'-15'	10'-15'	15' - 25'	10' - 15'	10'-15'	10'-15'
O Uplight	-	-	-	-	-	✓	-	-	-	-	-	-	-
Field Adjustable Wattage Selector (FAWS)	✓	✓	✓	-	✓	-	✓	-	-	-	-	-	-
DALI	✓	✓	✓	✓	✓	✓	✓	-	-	✓	-	-	-
Sensor Ready Driver	✓	✓	✓	✓	✓	✓	✓	-	-	✓	-	-	-
Service Tag	✓	✓	✓	-	✓	✓	✓	-	-	-	-	-	-
Photocell	Button Eye, Twist Lock	Button Eye, Twist Lock	Button Eye, Twist Lock	Button Eye, Twist Lock	Button Eye, Twist Lock	Button Eye, Twist Lock	Button Eye, Twist Lock	Button Eye	Button Eye	Button Eye, Twist Lock	Button Eye	Button Eye	Button Eye
Receptacle	3 pin, 7 pin	3 pin, 7 pin	3 pin	3 Pin, 7 Pin	7 Pin	7 Pin	3 pin, 7 pin	-	-	3 Pin, 7 Pin	-	-	-
Shielding	-	-	-	H	H	-	-	-	-	H	-	-	-
Additional Surge Protection	✓	✓	✓	✓	✓	✓	✓	-	-	✓	-	-	-
Finish	Black, White, Verde, Bronze, Green	Black, White, Verde, Bronze, Green	Black, White, Verde, Bronze, Green	Black, White, Verde, Bronze, Green	Black, White, Verde, Bronze, Green	Black, White, Verde, Bronze, Green	Black, White, Bronze, Green (Smooth & Textured)	Black, White, Bronze, Green, Grey	Black, White, Bronze, Green, Grey	Black, White, Verde, Bronze, Green, Grey	Black, White, Bronze, Verde, Forest Green	Black, White, Bronze, Green, Grey, Verde	Black, White, Bronze, Green, Grey, Verde
IP Rating	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66	-	-	-
Vibration	1.5G	1.5G	1.5G	1.5G	1.5G	1.5G	1.5G	-	-	1.5G	-	-	-
DLC Listing	✓	✓	✓	-	-	-	-	-	-	-	-	-	-
Certifications	cETLus	cETLus	cETLus	cETLus	cETLus	cETLus	cETLus	cETLus	cETLus	cETLus	cETLus	cETLus	cETLus
Lifetime Per TM21	L70 > 100,000 hrs	L70 > 100,000 hrs	L70 > 100,000 hrs	L70 > 50,000 hrs	L70 > 60,000 hrs	L70 > 60,000 hrs	L70 > 100,000 hrs	L70 > 54,000 hrs	L70 > 54,000 hrs	L70 > 54,000 hrs	L70 > 50,000 hrs	L70 > 50,000 hrs	L70 > 50,000 hrs
Limited Warranty	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years
Link													