

Featuring a range of traditional designs, providing style and elegance to parks, downtown streets, campuses and residential communities. They also offer a range of optical distributions and aesthetic options such as panels, FAWS, sensor ready, receptacle and shielding to customize your solution.



	Best	Best	Best	Best	Best	Best	Better	Better	Good	Good	Good	Good
Category / Style	Historical Square Lantern	Historical Hexagon	Historical Square Lantern	Historical Square Lantern	Historical Octagon	Historical Square Lantern	Historical Square Lantern	Historical Square Lantern	Historical Hexagon	Historical Square Lantern	Historical Hexagon	Historical Square Lantern
Product	<b>Independence</b>	<b>Architectural</b>	<b>Baltimore Large</b>	<b>Baltimore Small</b>	<b>New London</b>	<b>Savannah</b>	<b>TownView</b>	<b>TownView</b>	<b>Grande Manor</b>	<b>Indian Wells</b>	<b>Manor</b>	<b>VintageView</b>
Prefix	VX151/VX152	VX600	VX681	VX651	VX8911	VX671	TVLN, TVLC	TVPC, TVPR	6134	28738	5534	VVLN, VVPC
Light Engine	LEDgine	LEDgine	LED Lamp Included	LED Lamp Included	LED Lamp Included	Mini						
Lumen Output Range	Up to 12,884	Up to 11,427	Up to 16,687	Up to 12,884	Up to 12,767	Up to 16,687	Up to 12,808	Up to 12,379	Up to 4,733	Up to 4,493	Up to 4,721	Up to 9,916
Efficacy	Up to 126 LPW	Up to 117 LPW	Up to 116 LPW	Up to 126 LPW	Up to 101 LPW	Up to 116 LPW	Up to 125 LPW	Up to 121 LPW	Up to 91 LPW	Up to 87 LPW	Up to 91 LPW	Up to 154 LPW
Distribution	Type II, III, III Wide, V	Type II, III, III Wide, IV, V	Type II, III, III Wide, IV, V	Type II, III, III Wide, V	Type II, III, III Wide, IV, V	Type II, III, III Wide, IV, V	Type II, III, III Wide, V	Type II, III, III Wide, V	Type V	Type V	Type V	Type III, V
Color Temp	2700K, 3000K, 4000K	3000K, 4000K	3000K, 4000K	2700K, 3000K, 4000K	3000K, 4000K	3000K, 4000K	2700K, 3000K, 4000K	2700K, 3000K, 4000K	3000K, 4000K	3000K, 4000K	3000K, 4000K	2700K, 3000K, 4000K
Panels	Clear, Frosted, Ribbed	Clear, Frosted	Clear, Frosted, Ribbed	Clear, Frosted, Ribbed	Clear, Frosted	Clear, Frosted, Ribbed	Open, Comfort Lens	Comfort Panel, Ribbed	Opal, Prismatic	Opal, Prismatic	Opal, Prismatic	Open, Comfort Panels
Fitter/POD	Standard	Standard	Standard	Standard	Standard	Standard	A, L4, L3, S2, S3, S4	A, L4, L3, S2, S3, S4	Standard	Standard	Standard	Standard
Roof	Standard	Standard	Standard	Standard	Standard	Standard	Square, Curved	Square, Curved	Standard	Standard	Standard	Square, Curved
Cage	Standard	Standard	Standard	Standard	Standard	Standard						
Finial	Standard	Standard	Standard	Standard	Standard	Standard	Cupola	Cupola	Standard	–	Standard	Cupola
Mounting Height Range	15' - 25'	15' - 25'	15' - 25'	15' - 25'	10' - 20'	15' - 25'	15' - 25'	15' - 25'	10' - 20'	10' - 15'	10' - 20'	10' - 20'
0 Uplight	–	–	–	–	–	–	✓ (TVLN)	–	–	–	–	✓ (VVLN)
Field Adjustable Wattage Selector (FAWS)	✓	✓	✓	✓	✓	✓	✓	✓	–	–	–	✓
DALI	✓	✓	✓	✓	✓	✓	✓	✓	–	–	–	✓
Sensor Ready Driver	✓	✓	✓	✓	✓	✓	✓	✓	–	–	–	–
Sensor Ready Receptacle	–	–	–	–	–	–	✓	–	–	–	–	–
Service Tag	–	–	–	–	–	–	✓	✓	–	–	–	✓
Photocell	Button Eye, Twist Lock	Button Eye	Button Eye	Button Eye	Button Eye, Twist Lock	Button Eye, Twist Lock	Twist Lock	Twist Lock	Button Eye	Button Eye	Button Eye	Twist Lock
Receptacle	3 Pin, 7 Pin	7 Pin	7 Pin	–	–	–	7 Pin					
Shielding	H	H	H	H	H	H	H	H	–	–	–	H
Additional Surge Protection	✓	✓	✓	✓	✓	✓	✓	✓	–	–	–	✓
Finish	Black, White, Verde, Bronze, Green	Black, White, Bronze, Green (Smooth, Textured)	Black, White, Bronze, Green (Smooth, Textured)	Black, White, Verde, Bronze, Forest Green	Black, Bronze, Forest Green, Verde, White	Black, Bronze, Forest Green, Verde, White	Black (Smooth, Textured)					
IP Rating	IP66	IP66	–	–	–	IP66						
Vibration	1.5G	1.5G	1.5G	1.5G	–	1.5G	3G	3G	–	–	–	3G
DLC Listing	–	–	–	–	–	–	✓	✓	–	–	–	✓
Certifications	cETLus	cETLus	cETLus	cETLus	cETLus	cETLus						
Lifetime Per TM21	L70 > 60,000 hours	L70 > 54,000 hours	L70 > 54,000 hours	L70 > 50,000 hours	L70 > 50,000 hours	L70 > 50,000 hours	L70 > 100,000 hours					
Limited Warranty	5 years	5 years	5 years	5 years	5 years	5 years						
Link												