

A photograph of three people working together on a laptop. A woman in the foreground, wearing glasses and a blue shirt, is looking at the screen. A man in a blue shirt is partially visible on the left. A woman in a tan jacket is leaning in from the right, looking at the screen. They are in an office setting with a large window in the background.

# GENLYTE SOLUTIONS

## Controls Product Guide

Signify  
interact

PHILIPS  
dynalite

# Genlyte Solutions offers controls solutions for any requirements and budget

## Benefits of Signify lighting controls

**Energy savings** – By using intelligent lighting systems features such as Adaptive Dimming and Dwell Time, lighting is only used when needed and adapted to occupancy patterns. Natural light is harvested, and supplementary lighting is adjusted accordingly, resulting in optimized environmental performance and minimized operating and maintenance costs.

**Scalability** – Signify control solutions adopt a flexible approach to accommodate building growth or churn – accommodating a building journey to be smarter, connected and adaptive to changing tenancies, staff numbers and space reformation. The same components can be used in a single-room application or in larger projects involving thousands of controlled units.

**Ease of installation and configuration** – Both are easier to install and take less time to configure than conventional technologies, allowing customers to activate the project quickly and in a cost-effective manner.

**Code compliance** – Whether it is Title 24, IECC, ASHRAE or Well Building standard, Signify control solutions are up to date with the latest building code. See product specifications for compliance details.

**Preset lighting control** – This is more than just on/off lighting control. Signify control solutions allow you to create ambiance and recall different lighting scenes to suit your mood and the occasion.

**Distributed control and monitoring** – With logic being distributed between various devices in the network, there is not a single point of failure. Moreover, you can configure, control and monitor all the lights and system components by adding network gateways.

**Flexibility in design** – When layouts or control methods require modification, changes can be carried out via a simple configuration tool, allowing facilities to easily adjust and respond to changing times.

**Advanced integration into other systems** – Signify control solutions offer a range of integration devices, network gateways and APIs to integrated lighting and work in conjunction with other systems, such as building management systems, access control, fire and safety systems etc.

**Human Centric Lighting** – With the combination of tunable white technology and smart controls, get the freedom to create different ambiances in offices, schools, retail spaces and healthcare environments. Create personalized lighting to match the activity or enhance the atmosphere in the space. Moreover, automatically mimic daylight patterns by adjusting color temperature and brightness levels with respect to time of day for optimal visual comfort.



# signify interact

Interact is a wireless, smart lighting system with luminaire-integrated, connected sensing technology. Interact can help make workplaces comfortable, secure and productive, while boosting energy savings to meet sustainability targets. Available in three tiers, Interact can help with every step of your smart lighting journey.

## Why choose Interact?

- A simple wireless system with a tiered approach to suit your specific needs.
- Out of the box energy savings of up to 75%<sup>2</sup> and up to 85%<sup>3</sup> with gateways\*
- No gateway, no IT support required
- No light point restrictions, no extra wiring
- Protect your day 1 investment and scale up to the next tier without replacing or retouching your day one lighting setup
- DLC and code compliant [ASHRAE 90.1 (2019), T24 (2019) and IECC (2018) building codes]
- Fast and easy commissioning and start up
- **Adaptive dimming** and **dwell-time** features enable the system to adapt to occupancy patterns in real time – delivering deep energy savings while maintaining occupancy comfort levels
- For more information go to:  
<https://www.interact-lighting.com/en-us/what-is-possible/about-interact>

# PHILIPS dynalite


When you choose Dynalite, you are selecting the world's finest lighting control system. Tried and tested in more than 30,000 projects, Dynalite has implemented some of the largest and most extensive control networks around the globe that can be used in any application, on any scale.

## Why choose Dynalite?

- Up to 85% energy savings with a distributed networked controls approach<sup>2,3</sup>\*
- True hybrid system allowing for 0-10V, Phase cut, PWM, DALI, DMX, switching all dimming options from one system
- Highly configurable – achieve any combination of sophisticated outcomes customized to the exact needs of each living space
- Get pre-configured room automation features
- Many different user interfaces from which to choose, supporting custom engraving to match your needs
- Operate as standalone or network your entire building for central management
- DLC and code compliant [ASHRAE 90.1 (2019), T24 (2019) and IECC (2018) building codes]
- For more information go to:  
[www.dynalite.org](http://www.dynalite.org)

### Start simple and lay the foundation

- Smart lighting with luminaire integrated occupancy and daylight sensor
- Simply connect the Interact ready luminaires, retrofit kits and lamps with the intuitive Interact Pro app through a Bluetooth connection.
- Add sensors, switches, 3rd party 0-10V or phase dimming luminaires.
- Set-up is simple and straightforward, just like SpaceWise: no need for additional wiring or access to the building's internet connection.
- Save up to 80% on installation and material cost compared with more complex systems.<sup>1</sup>
- Boost energy savings up to 75% with the unique adaptive dimming and dwell time features.<sup>2</sup>




### Add a gateway for more benefits

- Instant access to cloud-based benefits and functionality such as scheduling, remote access, adaptation and energy monitoring, light point information regarding lifetime and health, as well as regular feature updates.
- Integrate with utilities for Open ADR based demand response strategy
- As your system grows, you can keep and build on all previously installed light points.



### Tap into the full potential of the IoT

- Access to occupancy, asset health and environmental sensing data
- Optimize workspace quality, improve safety and productivity and boost employee engagement – even across multi-sites.
- Unlock more savings with BMS integration
- Minimize waste with real time way-finding and desk/room booking tools



1. Compared to installation of wired networked lighting control systems.


2. Based on installation in the GSA-operated Metcalfe Federal Building located in Chicago, Illinois. This project was installed under the GSA Green Proving Ground Program. <https://www.assets.signify.com/is/content/Signify/Assets/phillips-lighting/united-states/20201013-gpg-findings-integrated-with-alc.pdf>

3. Additional savings derived from HVAC, plug load control integrations and optimizing performance based on usage trends.


## Functionalities overview

		Standalone	Gateway	Gateway + IoT
Meet building codes	Integrated occupancy and daylight sensing	✓	✓	✓
	Manual ON	✓	✓	✓
	Partial automatic ON	✓	✓	✓
	Multi-level continuous dimming	✓	✓	✓
	Automatic shut-off control	✓	✓	✓
	Automatic daylight responsive control	✓	✓	✓
	Dimming, daylight harvesting & occupancy controls	✓	✓	✓
	Automatic receptacle control (Plug load control)	✓	✓	✓
	Outdoor Parking Sensor*	✓	✓	✓
	UL924 Emergency	✓	✓	✓
Comply with DLC	Automatic Demand Responsive controls (Open ADR)	✓	✓	✓
	Networking of luminaires and devices	✓	✓	✓
	Luminaire Level Lighting Control (LLLC, integrated)	✓	✓	✓
	High-end trim	✓	✓	✓
	Zoning	✓	✓	✓
	Individual addressability	✓	✓	✓
Maximize energy savings, rebates & comfort	Cybersecurity	✓	✓	✓
	Adaptive dimming (light when you need it, where you need it)	✓	✓	
	Dwell time	✓	✓	
	BlueTooth (BLE) connectivity (for commissioning only)	✓	✓	✓
	Scene control	✓	✓	✓
	Personal control for a single user	✓	✓	✓
	Energy reporting and export	✓	✓	✓
	Scheduling	✓	✓	✓
Beyond code	Device monitoring/remote diagnostics	✓	✓	
	Circadian lighting support	✓	✓	✓
	Remote management	✓	✓	✓
	Multi-site management	✓	✓	✓
	Floor plan visualization		✓	
	Occupancy analytics (heatmaps)		✓	
	BACnet integration		✓	
	APIs (light control, occupancy, people count)		✓	
IoT features	Physically swap/upgrade sensors		✓	
	Room booking via App (e.g. meeting room reservation)		✓	
	Interface for Outlook and Google calendar integration		✓	
	Desk booking via App		✓	
	People estimation (via SC1500 sensor, and people counting supported via external PointGrab sensor)		✓	
	Temperature & humidity sensing (via SC1500 sensor)		✓	
	Noise classification sensing (via SC1500 sensor)		✓	
	Wayfinding via App		✓	
	Indoor positioning SDK		✓	
	IoT Apps: Kiosk App, Space Management App, Workspace App		✓	

## Interact supported devices


Sensing and control devices				
				
Interact-ready wireless luminaires	Commissioning device (IRT9015)	Wireless scene switches Options for battery-powered, self-powered, and mains-powered switches		Wireless load controller with 0-10V (SWCS-RADIO / SWCS-SNSR-R-S)
				
Multi-sensor bundle for Gateway + IoT (SC1500)	0-10V or Phase control modules (SBAZ10-CS or SBAELS-CS)	Sensor SNH210IA (SWZCSH)	Outdoor parking sensor (LCN4120/05, LCN4120/15, LCN4150/05, LCN4150/15)	Outdoor repeater for parking applications

Add-on gateways for system monitoring		
		

Software suite			
			

# Interact system architecture for office, education, healthcare, retail and industrial applications

## Gateway + IoT



## Gateway

Wireless gateway

Wireless gateway

## Standalone



Interact  
Pro app




Wireless switch  
relay controller  
(plug load, relay, dimming)



Luminaires with wireless  
integrated sensor



0-10V control  
module



Phase dimming  
module



Wireless repeater  
and controller for  
exterior applicatons



Commissioning  
remote



Wireless  
wall switch



External battery  
powered sensor




Smart  
LED lamp



Site & area  
luminaire with  
sensor



Parking garage  
luminaire with  
sensor



A one-stop solution with stand-alone or multi-system capabilities, featuring a strong hardware portfolio with maximum software and system integration flexibility.

## Choose your desired level of control


- Save up to 75%<sup>2</sup> energy with occupancy and daylight sensor based controls. Up to 85%<sup>3</sup> savings with integration to HVAC, plug load and other sub-systems.
- Independent functionality with distributed intelligence and no single point of failure.
- Integrate your lighting controls with HVAC, blinds and AV systems with a comprehensive range of integration devices.
- Be it DALI, 0-10V, DMX, relay or phase dimming, the system offers flexibility around multiple dimming protocols.
- Deploy as standalone controls or network multiple spaces together for central monitoring and management.
- Choose design options from the award winning [Antumbra](#) user interfaces for chic look and feel.

See how the hardware, protocols, and software work together with ease

- All Dynalite system components (hardware, protocols and software) directly complement each other, granting every device on the network access to all the system features and functions as needed.

## Get the ultimate end-user experience with System Manager

- System Manager is the dedicated head-end software for Dynalite systems. With direct access and oversight across the entire system, this application presents the most advanced and powerful features in an intuitive and representative format, enabling true end-user ownership of system operations.
- It includes maintenance tools, detailed reports of energy usage, lighting status, and system performance, paired with an easy-to-use console along with clear and concise floor plans.



<sup>2</sup>Based on installation in the GSA-operated Metcalfe Federal Building located in Chicago, Illinois. This project was installed under the GSA Green Proving Ground Program. <https://www.assets.signify.com/is/content/Signify/Assets/phillips-lighting/united-states/20201013-gpg-findings-integrated-with-alc.pdf>

<sup>3</sup> Additional savings derived from HVAC, plug load control integrations and optimizing performance based on usage trends.

## Functionalities overview

		Controls	System Manager
Meet building codes	Ceiling and wall mounted occupancy and daylight sensing	✓	✓
	Manual ON	✓	✓
	Partial automatic ON	✓	✓
	Multi-level continuous dimming	✓	✓
	Automatic shut-off control	✓	✓
	Automatic daylight responsive control	✓	✓
	Automatic receptacle control (Plug load control)	✓	✓
	UL924 Emergency	✓	✓
	Automatic Demand Responsive controls (Open ADR)	✓	
Comply with DLC	Networking of luminaires and devices	✓	✓
	High-end trim	✓	✓
	Zoning	✓	✓
	Individual addressability	✓	✓
	Cybersecurity	✓	
Maximize energy savings, rebates & comfort	Adaptive dimming (at an area level)	✓	✓
	Tunable white and color control	✓	✓
	Dwell time	✓	✓
	Scene control	✓	✓
	Scheduling	✓	✓
	Personal control		✓
	Energy reporting and export		✓
Beyond code	Device monitoring/remote diagnostics		✓
	BACnet integration	✓	✓
	Advanced integration (A/V, blinds, motor etc)	✓	✓
	Multi-protocol support (DALI, DMX, 0-10V, phase)	✓	✓
	Pre-configured solutions (eg. Room automation system, UVC controls)	✓	✓
	Multi-site management		✓
	Floor plan visualization		✓
	Occupancy analytics (heatmaps)		✓
IoT features	User profiles and role based permissions		✓
	Temperature & humidity sensing (via Antumbra & Revolution UIs)	✓	✓
	IoT Apps: iOS and Android	✓	✓
	Remote upgrades: Software and firmware upgrades over the network		✓
	APIs (light control, curtain control)		✓


## Wired Controls

### Dynalite controls devices

User interfaces					
					
AntumbraButton (PAXBPA)	AntumbraDisplay (PADPA)	AntumbraTouch (PATPA)	Revolution Series (PDRxA)	DyNet Communication Module (D ACM-DyNet)	Networked Touchscreen (PDTS)
Sensors					
					
Multifunction Sensor (DUS360CR)	Multifunction Sensor (DUS360CS)	Multifunction Sensor DALI (DUS360CS-D)	Multifunction Sensor (DUS804CS-UP)	Multifunction Sensor 90° (DUS90CS)	Multifunction Sensor 30° (DUS30CS)
Relay controllers					Power dimmers
					
Multi-Protocol Switching Room Controller (DDRC-GRMS-E)	4 Channel Relay Controller (DDRC420FR)	8 Channel Relay Controller (DDRC810DT-GL)	12 Channel Relay Controller (DDRC1220FR-GL)	PWM Controller (DDLEDC605GL)	
Signal dimmers					
					
DALI-2 Driver Controller, 1 DALI universe (DDBC120-DALI)	DALI-2 Driver Controller, 3 DALI universes (DDBC320-DALI)	Signal Dimmer Controller, 5 Channel (DDBC516FR)	Signal Dimmer Controller, 12 Channel (DDBC1200)	J-Box Mounted Controller (DDC116)	
Multipurpose controllers					
					
Multipurpose Modular Controller + Control Modules (DDMC802)	Multipurpose Modular Panel + Control Modules (DMC2)	Multipurpose Modular Panel + Control Modules (DMC4)			

Integration devices				Electrical accessories	
RS-232 Network Gateway (DDNG232-NA)	BACnet Network Gateway (DDNG-BACnet)	Dry Contact Interface (DLLI8I80)	Low Level Input Integrator (DDMIDC8-NA)	Network Power Supply (DMNP24040-P-NA)	DIN Rail Enclosure (DH2X24)
Network devices					
Ethernet Gateway - Supervisor (PDDEG-S)	Ethernet Gateway (PDEG)	RS-485/DMX512 Gateway (DDNG485-NA)	PC Node (DTK622-USB-J-NA)	Serial Port Node (DMNG-232-NA)	Serial Port Node (DMNG-USB-NA)
Software and Apps				Wired System	
Dynalite System Manager	Dynalite System Builder	Dynalite Control App	Dynalite EnvisionTouch	Dynalite DynamicTouch	Preassembled UL-rated multi-purpose control cabinets (ULCx)

## Dynalite system architecture



## Room Automation System (PDRAS)

### Single-box solution

- Assembled, programmed, and tested in the factory to provide complete out-of-the-box functionality.

### Multi-zone support

- Each control system can manage up to five separate zones in single- or dual-room applications.

### Networked Multifunction sensor

- Reduce installation complexity and ceiling/plenum clutter with combined occupancy and light level (lux) detection.

### Optional networked PIR and ultrasonic sensors

- Expand your system's occupancy detection footprint with up to three extra PIR sensors and/or one long-range ultrasonic sensor per room. Sensors communicate with each other so that their combined occupancy status determines the system response.

### Integrated daylight harvesting

- Multifunction sensors micro-adjust lighting levels to meet energy management regulations without disrupting occupant comfort.

### Stations with large buttons and simple labelling

- Ensures straightforward operation for non-technical users.

### UL924 input

- Integrates seamlessly with compatible emergency systems.

### Direct-drive relays

- Isolate power to lighting groups and wall outlets to eliminate standby power consumption

### Software-selectable 1-10V / DALI control

- Although factory-set for 1-10V, each control channel can be individually configured for DALI operation using Dynalite's System Builder commissioning software on a connected PC or laptop.


### Ethernet connectivity\*

- Enables network access to the school LAN for centralized monitoring and management.


\* Future provision for -E variants only, not enabled at release.




# Philips Dynalite Room Automation System architecture



## Single room system



## Dual room system



! Only one ultrasonic sensor per room

! Sensor placement depends on local architecture

## Single Zone Controller

**20 Amp relay and dimming control**  
of 0-10 V and DALI broadcast drivers

**Suitable for plenum use**  
UL 2043 certified for installation  
in air-handling plenum spaces

**Inbuilt diagnostic functionality**  
Features Device Online/Offline  
status indication

**Universal voltage**  
100-277 VAC, 50 mA current sink

**1x dry contact input for UL924**

### Standalone or networked

Suitable for room-based applications  
or integration across multiple spaces

### Accepts DMX 512 input

**Easy to install**  
Snap on RJ45 ethernet connectors

### Flexible



Control 0-10V, DALI broadcast

### Daisy chain devices

Connect additional controllers  
or other devices

### Compact design

Fits into standard junction box housings



## PDUVCC-NA system architecture

## Dedicated Standalone Devices

DDC116

**DDC116** – Single zone 0-10v/Relay Controller

**PABPA-SSA** – 7 Different engravings with 15 configurations

**DACM-SSA** – Configurable Antumbra Comms Module

**DUS804CS-UP-SSA-O or DUS804CS-UP-SSA-V** – Preconfigured Ultrasonic Sensor

- and/or -

**DUS360CS-DA-SSA** – Configurable PIR/Daylight sensor



## System Behavior

All devices that are linked together through DyNet wiring will behave as a control area and deliver a unified system behavior.

PABPA-SSA




## Sensor

- Sensor configurable between occupancy (default) or vacancy mode
- Configurable timeouts of 5, 10, 15, and 20min (default)
  - 1 min grace period on all timeouts
  - 20min witness mode to test functionality
- Built-in daylight sensing
  - Flexibility to activate primary and secondary daylight zones

## Switches

- Recall preset lighting scenes
- Ramping disables daylight harvesting
- Ramping buttons only affect zones that are lit or “on”
- Fully customizable configuration via **System Builder**  
for more demanding projects

DACM-SSA



DUS804CS-UP-SSA-O or  
DUS804CS-UP-SSA-V



and/or



DUS360CS-DA-SSA



© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

SGn-2161PG\_Controls\_product\_guide 01/26



a business

Signify North America Corp.  
400 Crossing Blvd, Suite 600  
Bridgewater, NJ 08807  
Telephone: 800-555-0050

Signify Canada Ltd.  
281 Hillmount Road,  
Markham, ON, Canada L6C 2S3  
Telephone: 800-668-9008

All trademarks are owned by Signify Holding or their respective owners.

[www.genlyte.com](http://www.genlyte.com)